



Nootboom MC0-48-03 2X UITSCHUIFBAAR

Características generales

Marca	Nootboom
Subcategoría	Semi-góndola rebajada
Fecha de primera inscripción	01-11-2005
Color	Rojo
Condición	Usado
Estado general	Bien
Referencia	1790816



Propiedades

Peso individual	16.050kg
Capacidad de carga	31.950kg
Peso bruto vehicular	48.000kg

Especificaciones técnicas

Número de ejes	3
----------------	---

Descripción

NOOTEBOOM MCO-48-03V 3-AXLE EXTENDABLE SEMI LOW LOADER / DOUBLE TELESCOPIC / HYDRAULIC STEERING / 48 TON NOOTEBOOM MCO-48-03V 3-AXLE DOUBLE EXTENDABLE SEMI LOW LOADER** **YEAR OF MANUFACTURE: 2005** **DATE OF FIRST REGISTRATION: 01-11-2005** **CHASSIS NUMBER: XMRMC000050000480** NOOTEBOOM MCO-48-03V SEMI LOW LOADER - 3-AXLE SEMI LOW LOADER TRAILER - DOUBLE TELESCOPIC / DOUBLE EXTENDABLE - HYDRAULIC DUAL-CIRCUIT STEERING SYSTEM - SELF-STEERING / FOLLOW-UP STEERING - EBS ELECTRONIC BRAKING SYSTEM - TYRE SIZE 235/75 R17.5 - TECHNICALLY PERMITTED MAXIMUM SPEED 80 KM/H - TECHNICALLY PERMITTED GROSS VEHICLE WEIGHT 48,000 KG - PERMITTED GROSS VEHICLE WEIGHT ACCORDING TO REGISTRATION DOCUMENTS 42,000 KG - EMPTY WEIGHT APPROX. 11,120 KG - PAYLOAD APPROX. 30,880 KG AT 42,000 KG GROSS WEIGHT - TECHNICAL AXLE LOAD 3 X 10,000 KG - FIFTH-WHEEL / KINGPIN LOAD 18,000 KG DIMENSIONS ACCORDING TO TECHNICAL DRAWING - WIDTH 252 CM - MAXIMUM DIMENSION HK-AZ 2,533 CM - LENGTH DIMENSION 1,223 + 640 + 670 = 2,533 CM - LENGTH DIMENSION 953 + 640 + 670 = 2,263 CM - LENGTH DIMENSION 961 + 640 + 670 = 2,271 CM - ADDITIONAL LENGTH DIMENSION 823 CM - FIRST TELESCOPIC EXTENSION 640 CM - SECOND TELESCOPIC EXTENSION 670 CM - TOTAL EXTENSION LENGTH 1,310 CM - LOADING HEIGHT APPROX. 91 CM (+7 / - 12 CM) - SUPPORT LEG HEIGHT ACCORDING TO DRAWING 93.5 CM (+7 / - 12 CM) - RADIUS R 175 CM - RADIUS R 235 CM - REAR AXLE SPACING DIMENSIONS 136 + 136 + 126 CM - AXLE GROUP DIMENSION 262 CM ADDITIONAL DIMENSIONS ACCORDING TO TECHNICAL DRAWING - 125.5 CM - 31 CM - 120 CM - 270 CM - 78 X 25 CM - 70 CM - 2 X 30 CM - 63 CM - 15.7 CM - DETAIL DIMENSION 31 X 6 CM CONTAINER DIMENSIONS ACCORDING TO DRAWING - 1 X 20 FT + 30 CM - 1 X 40 FT + 30 CM VEHICLE DIMENSIONS ACCORDING TO REGISTRATION DOCUMENTS VARIABLE OVERALL LENGTH APPROX. 1,335 TO 2,675 CM PLEASE NOTE:** THE TECHNICAL DRAWING AND THE VEHICLE REGISTRATION DOCUMENTS USE DIFFERENT MEASUREMENT POINTS AND DIMENSIONS. WEIGHTS AND PAYLOAD - TECHNICALLY PERMITTED GROSS VEHICLE WEIGHT 48,000 KG - PERMITTED GROSS VEHICLE WEIGHT ACCORDING TO REGISTRATION 42,000 KG - EMPTY WEIGHT APPROX. 11,120 KG - PAYLOAD APPROX. 30,880 KG - TECHNICAL AXLE LOAD 10,000 KG PER AXLE - FIFTH-WHEEL / KINGPIN LOAD 18,000 KG SPECIAL FEATURES VERY INTERESTING NOOTEBOOM MCO-48-03V 3-AXLE DOUBLE TELESCOPIC SEMI LOW LOADER, EQUIPPED WITH TWO TELESCOPIC EXTENSIONS OF 640 CM AND 670 CM RESPECTIVELY. THE TRAILER IS EQUIPPED WITH A HYDRAULIC DUAL-CIRCUIT STEERING SYSTEM WITH FOLLOW-UP STEERING, PROVIDING EXCELLENT MANOEUVRABILITY WHEN TRANSPORTING LONG AND HEAVY LOADS. THANKS TO ITS DOUBLE TELESCOPIC EXTENSION SYSTEM, OFFERING A TOTAL EXTENSION LENGTH OF NO LESS THAN 13.10 METRES, COMBINED WITH HYDRAULIC STEERING, THIS NOOTEBOOM SEMI LOW LOADER IS PARTICULARLY SUITABLE FOR TRANSPORTING LONG, HEAVY AND OVERSIZED LOADS. **IDEAL FOR:** - CONSTRUCTION MACHINERY TRANSPORT - HEAVY HAULAGE - LONG LOAD TRANSPORT - STEEL STRUCTURES - INDUSTRIAL TRANSPORT - SPECIAL AND

Accesorios

- ABS
- Suspensión neumática