



Faymonville STBZ-2VA UITSCHUIBAAR

General characteristics

Brand	Faymonville
Subcategory	Lowloader
Date of first registration	19-03-2004
Colour	Green
Condition	Used
General state	Good
Reference	1790782



Properties

Single weight	13.400kg
Load capacity	22.600kg
GVW	36.000kg
Length	1.560cm
Width	255cm

Technical specifications

Number of axes	2
----------------	---

Description

FAYMONVILLE STBZ-2VA – 2 AXLE LOWLOADER – EXTENDABLE – DETACHABLE GOOSENECK – HYDRAULIC STEERING **Very clean and robust Faymonville STBZ-2VA 2-axle lowloader**, equipped with a **detachable gooseneck, extendable low bed, hydraulic steering on both axles, air suspension and central lubrication system**. A professional heavy-duty lowloader, ideally suited for the transport of construction machinery, excavators, wheel loaders, cranes and other heavy or long equipment. GENERAL INFORMATION ***Make:** Faymonville ***Type:** STBZ-2VA ***Execution:** 2-axle lowloader * **Date of first registration:** 19-03-2004 ***Number of axles:** 2 ***Axles:** BPW ***Both axles hydraulically steered*** **Air suspension*** **Central lubrication system*** **Detachable gooseneck*** **Excavator boom recess at the rear*** **Tyres:** 235/75 R17.5 LOW BED / LOADING PLATFORM This Faymonville is equipped with an extremely low and extendable loading platform. * **Low bed length retracted:** approx. 840 cm * **Extendable by:** approx. 550 cm * **Maximum low bed length extended:** approx. 1,390 cm * **Loading platform width:** approx. 255 cm * **Loading floor height:** only approx. 45 cm * **Loading floor thickness:** approx. 24 cm Thanks to the extremely low loading floor height of only approximately **45 cm**, this lowloader is particularly suitable for transporting high machinery where keeping the overall transport height as low as possible is essential. The loading platform can be extended by an impressive **5.50 metres**, making this trailer also very suitable for transporting long machinery, constructions and special equipment. DETACHABLE GOOSENECK Equipped with a **detachable gooseneck**, allowing self-propelled machinery to be loaded directly from the front onto the low loading platform. Ideally suited for transporting: * Excavators * Crawler excavators * Bulldozers * Wheel loaders * Crawler cranes * Road construction machinery * Agricultural machinery * Heavy construction equipment * Special machinery AXLES & CHASSIS Equipped with **2 BPW axles**, with **both axles hydraulically steered**. The hydraulic steering provides excellent manoeuvrability, especially on confined construction sites, industrial locations and during special transport operations. The trailer is also equipped with **air suspension**, providing excellent driving characteristics and good load distribution. WEIGHTS * **Total weight:** approx. 36,000 kg * **Empty weight:** approx. 15,600 kg * **Stated payload:** approx. 22,600 kg **Please note:** the stated weights should be checked against the official vehicle documents, as the empty weight and stated payload together amount to 38,200 kg. DIMENSIONS ***Overall lowloader length:** approx. 1,560 cm * **Overall width:** approx. 255 cm * **Low bed length retracted:** approx. 840 cm * **Extension:** approx. 550 cm * **Maximum low bed length extended:** approx. 1,390 cm * **Loading floor height:** approx. 45 cm * **Loading

Accessories

- Anti-lock braking system
- Air suspension
- Central lubrication
-